



ROAR!
with us.



Laminated Fiberglass Filter

Laminated fiberglass top mount & side mount filter is durable, corrosion-resistant, glossy finished in gel coats for a smooth and beautiful exterior, which is popular in the market. This collection of sand filters is the perfect choice for high-end villas and hotel pools, high-class spas and wellness pools, baths, fish ponds & etc.


- ▶ Non corrosive gel coat fiberglass tank, smooth finished
- ▶ Equipped with a 1.5" or 2.0" six-position multiport valve
- ▶ Universal standard of union connection provided
- ▶ Max. working pressure 36 psi/2.5 bar
- ▶ Max. temperature of 43° C (109° F)
- ▶ Suggested size of media : 0.5 - 0.8 mm.



Laminated Fiberglass Top Mount Filter

Specification and size


Model	Max flow rate		Filter area m ²	Port size		sand kg	Dimension (mm)					
	lpm	m ³ /h		inch	mm		A	B	C	D	E	F
Multiport valve 1.5												
FL550T	167	10.00	0.20	1.5"	50	88	886	750	690	390	530	286
FL650T	275	16.50	0.33	1.5"	50	158	1000	850	790	500	640	318
Multiport valve 2.0												
FL750T	366	22.00	0.44	2.0"	63	260	1170	1005	920	710	750	390
FL800T	420	25.00	0.50	2.0"	63	350	1200	1030	950	710	800	420
FL900T	533	32.00	0.64	2.0"	63	422	1295	1160	1080	710	900	450



Laminated Fiberglass Side Mount Filter

Specification and size

Model	Max flow rate		Filter area m ²	Port size		sand kg	Dimension (mm)					
	lpm	m ³ /h		inch	mm		A	B	C	D	E	F
Multiport valve 1.5												
FL550	167	10.00	0.20	1.5"	50	100	835	635	390	530	125	300
FL650	275	16.50	0.33	1.5"	50	150	900	680	500	640	125	320
Multiport valve 2.0												
FL750	366	22.00	0.44	2.0"	63	250	950	750	710	750	220	350
FL800	420	25.00	0.50	2.0"	63	300	1005	785	710	800	220	360
FL900	533	32.00	0.64	2.0"	63	375	1110	850	710	900	220	405





ROAR!
with us.



Bobbin-wound Fiberglass Filter

Bobbin-wound fiberglass top mount & side mount filter is made of high quality fiberglass and resin, the fiberglass winding structure makes the sand filter more stronger, there's UV-resistant on the surface, the whole filter has good resistance to chemical and sun protection. This collection is the first choice for water treatment equipment at swimming pools, hot springs, spas, aquariums, water parks & etc.



- ▶ UV-resistant surface finished.
- ▶ Equipped with a 1.5" or 2.0" six-position multiport valve
- ▶ Universal standard of union connection provided
- ▶ Max. working pressure 36 psi/2.5 bar
- ▶ Max. temperature of 43° C (109° F)
- ▶ Suggested size of media : 0.5 - 0.8 mm.



Bobbin-wound Fiberglass Top Mount Filter

Specification and size

Model	Max flow rate		Filter area m ²	Connection		sand kg	Dimension (mm)					
	lpm	m ³ /h		inch	mm		A	B	C	D	E	F
Multiport valve 1.5												
FB400T	105	6.00	0.13	1.5"	50	30	740	590	530	175	410	390
FB450T	135	8.10	0.16	1.5"	50	45	770	610	550	210	460	390
FB550T	185	11.10	0.22	1.5"	50	85	830	720	660	235	530	390
FB650T	260	15.60	0.32	1.5"	50	145	980	820	760	300	640	500
Multiport valve 2.0												
FB700T	336	20.16	0.41	2.0"	63	215	1083	930	870	390	700	500
FB750T	390	23.00	0.44	2.0"	63	230	1150	980	900	430	750	710
FB800T	415	24.90	0.50	2.0"	63	355	1200	1020	950	425	800	710
FB900T	520	31.20	0.64	2.0"	63	470	1310	1160	1080	480	900	710
FB1000T	650	39.00	0.79	2.0"	63	620	1410	1250	1160	580	1000	710
FB1100T	700	42.00	0.98	2.0"	63	700	1500	1330	1250	630	1100	890
FB1200T	860	51.60	1.13	2.0"	63	860	1590	1390	1300	740	1200	890
FB1400T	950	57.00	1.54	2.0"	63	1400	1800	1600	1510	850	1400	1200



Bobbin-wound Fiberglass Side Mount Filter

Specification and size

Model	Max flow rate		Filter area m ²	Connection		sand kg	Dimension (mm)						
	lpm	m ³ /h		inch	mm		A	B	C	D	E	F	G
Multiport valve 1.5													
FB550	185	11.10	0.22	1.5"	50	85	390	450	640	235	530	390	125
FB650	260	15.60	0.32	1.5"	50	145	450	510	750	300	640	500	125
Multiport valve 2.0													
FB700	336	20.16	0.41	2.0"	63	215	520	610	850	390	700	500	220
FB750	390	23.00	0.44	2.0"	63	250	540	620	920	390	750	710	220
FB800	435	24.10	0.53	2.0"	63	355	570	650	980	425	800	710	220
FB900	495	29.70	0.66	2.0"	63	470	640	730	1110	480	900	710	220
FB1000	670	40.20	0.82	2.0"	63	620	700	770	1190	580	1000	710	220
FB1100	700	42.00	0.98	2.0"	63	700	740	820	1290	680	1100	890	220
FB1200	880	52.80	1.17	2.0"	63	860	780	860	1380	740	1200	890	220
FB1400	950	57.00	1.54	2.0"	63	1400	820	900	1590	800	1400	1200	220

